

SMARTPHONE MOUNT

The Rowing in Motion Smartphone Mount is designed to optimally attach your smartphone to a rowing shell by ensuring it stays in a fixed position and dampening vibrations that affect the quality of measurement.

This mount supports two modes of operation and is easily portable between boats:

- mounting on a wing rigger using the supplied self-locking Velcro straps
- mounting on a straight surface using 3M Dual Lock adhesive pad

△ Always use a waterproof case with your smartphone, unless the phone is rated waterproof by the manufacturer. We do not accept any liability for possible water-damage to your phone.

1. Getting Started

To get started, you need to apply the supplied 3M Dual Lock synthetic Velcro pads to your smartphone(-case) and the boat (for deck mount only).

Dual Lock pads must be applied at **room temperature** and all surfaces must be **clean, dry, and free of oil and lint**. Use

the supplied cleaning swab or a similar cloth soaked with an appropriate solvent to clean the surface.

△ The adhesive used on the supplied Dual Lock requires 24 hours to cure to maximum strength. Don't get it wet until it is fully cured.

2. Preparing your Smartphone

To mount your smartphone or smartphone-case onto the faceplate of the bracket you will need to stick the 4 small pads in the appropriate position on your smartphone. We recommend you position your smartphone(-case) to align with the bottom edge of the faceplate so that it doesn't touch the boat when you mount the bracket on the deck (see section 4).



1: FACEPLATE OF THE BRACKET ON A WING RIGGER WITH PADS FOR SMARTPHONE

Then “click” the supplied dual lock tapes into their counterparts on the face plate and ensure the wave-pattern of the pins matches. Do a “dry-run” to find the right position on your smartphone(-case). Clean the surface using the supplied cleaning swab and remove the protective tape from the pads. Carefully position your smartphone(-case) in its final position and gently press it down into the dual lock pads. Hold it down for at least 30 seconds and leave it on the face-plate for at least 10 minutes to give the adhesive a chance to cure. Then remove the smartphone(-case) from the faceplate using a **peeling motion**. Apply gentle pressure to each pad with your fingertip to ensure they are fully bonded.

*△ When removing your smartphone **do not pull straightly** on it as this will put a lot of force on the dual lock pads and the smartphone. Use a careful peeling motion instead to detach the smartphone safely.*

3. Mounting on a Wing Rigger

To mount the bracket on a wing rigger use the supplied detachable Velcro straps as shown in figure 1. Hold the bracket on the face of your wing rigger so that both foam paddings on the inner side of the bracket contact the rigger. Wrap one strap around the rigger and thread it back through the eyelet. Repeat this with the second strap

before pulling both straps tight and closing them.

⚠ Do not pull the straps overly tight, especially on a carbon wing rigger. "Nach fest kommt ab".

Pro Tip: Leave the tip of the Velcro "open" so that you can easily grab it when you want to open the strap to remove the mount.



2: CORRECT ATTACHEMENT OF VELCRO STRAPS ON THE BRACKET

4. Mounting on the Deck

The mounting bracket can also be attached to any straight surface such as the deck of the boat. This is most useful behind the stretcher of the stroke seat (see figure 3) or in front of the cox. The underside of the bracket has a single large Dual Lock pad that hooks into the supplied counterpart pad. Follow the instructions about working

with Dual Lock in section 1 to attach the supplied pad to your position of choice.



3: BRACKET MOUNTED ON THE DECK WITH SMARTPHONE

Pro Tip: Ensure the bracket is orthogonal to the centerline of the boat for optimum measurement accuracy.

You can detach the Velcro straps from the mounting bracket for deck mounting by carefully threading them through the destined slots in the bracket. Refer to figure 2 when reattaching them.

Care Instructions

The adapter is made from solid brushed stainless steel and needs no maintenance beyond reasonable cleaning. Even though we use a high quality stainless steel, the bracket may corrode when in contact with salt water. You can clean the exposed steel parts with a damp cloth.

⚠ The adhesive used on the supplied Dual Lock forms a very strong bond with the surface. Should you want to remove the pads use a hairdryer to warm them thoroughly, then slowly peel from one edge to avoid damage to the surface.

Accessories

You can order a spare set of Dual Lock with pads for an additional smartphone or deck mount from our online shop at <https://www.rowinginmotion.com>.

Warranty

We provide a two year warranty from the date of purchase for this product when handled properly and accordingly to our instructions. We guarantee this product to be free of defects in materials and workmanship and will repair or replace any defective product or parts when notified within the warranty period.

Should you require assistance with the installation or operation of this product or want to arrange a repair, please don't hesitate to get in touch with us at support@rowinginmotion.com.

Made in Germany